engelfried MASCHINIENTECHNIK

MACHINE-DATA

Machinetype : Sanding machine

Make : LÖWER

Type : LZ DBx2-200 Crossmaster

Year : neu
Control type :
Control :

Storage location : ab Werk
Origin : Germany

Delivery time : after arrangement

Quotation : ex work
Price : on request



TECHNICAL DATA

Number of sanding units 4 St. sanding width 200 mm Sanding height max. 150 mm

TECHNICAL DESCRIPTION

LÖWER CrossMaster DBx2-200

for the finish sanding and intermediate sanding of all strips Type with simultaneous processing from above and below

- 1 disc sanding flap unit each from above and

bottom, D= 200mm, 0.75 kW,

- Continuous speed control of the disc units

200-600 rpm via frequency converter

- 1 grinding flap roller each from above and below, D = 270mm,

B=150mm, counter rotation, 0.75kW each,

- Continuous speed control of the grinding spindles

200-1000 rpm, via frequency converter

- Staggered arrangement of the sanding units, each at the top and bottom

Below, grinding flap disc with subsequent grinding flap roller

- Working width max. 200mm
- Safe conveyor belt feed (top and bottom).

spring-loaded pressure rollers, transport belt width 200mm

- continuous feed 4-20m/min

Geared motor 1.5 kW and frequency converter

- motorized workpiece thickness adjustment 30-150mm above

Geared motor including digital display

Technical specifications according to manufacturer's information / documentation

Sanding machine

LÖWER

LZ DBx2-200 Crossmaster

Stock no. :1305-5282



- Separate adjustment option for the disc in height and lateral direction relative to the following roller, as well Separate delivery option for the rollers
- Inlet contact with emergency stop interruption
- complete machine encapsulation with suction nozzle 1 x 150mm
- Operating voltage: 400 volts, 50 Hz, 3P
- Length x width x height (mm): 1900x850x1800
- Weight: 600kg
- CE version

Price of the above machine on request!

Special accessories with additional costs:

Soft disc aggregates

top and bottom for intensive cross-cutting and fine sanding including sensor-controlled automatic immersion instead Grinding flap discs

Guide ruler

for supporting profiled window bars in the machine, Ruler with support rollers throughout the entire machine mounted on the left side, precisely adjustable in height via a Handwheel with 1/10mm counter, can be moved sideways Clamping pieces against stops (in use/not in Use)

Workpiece blow-off at the machine outlet

Set of SmartFlex sanding flaps for CrossMaster DBx2-200 consisting of: 48 strips M 55 / 200 (rolls) 60 strips M 35 / 50 (discs)

Set of SmartFlex sanding flaps for CrossMaster only for lamella roller consisting of: 48 strips M 55 / 200

Sandpaper disc VB for soft disc D=200mm grit 280 with velor backing (Velcro), pack of 100.

Price of the above-mentioned special accessories on request!

(technical information according to the manufacturer - no guarantee!)
All prices quoted are net. plus statutory VAT

Technical specifications according to manufacturer's information / documentation



VIDEO-LINKS

WEB-LINK

https://lagermaschinen.de/maschinen-datenblatt/Sanding_machine/LOeWER/LZ_DBx2-200_Crossmaster/1305-5282



MACHINE PICTURES







